

Technical Datasheet

Primer S

Product Description: Clear acrylic primer intended to reinforce surface before application of topcoats paints.

Typical Uses: Applied in one coat in new construction on interior walls after application of Gold Bond and before application of topcoat. Also used on existing walls where old paint has been scraped and rubbed or after defects in walls have been repaired.

Surface Preparation: After removal of peeling paint from an old wall, smooth the surface with sandpaper and clean to remove dust, before application of Primer S. On plaster walls smooth the spackle between the boards and clean to remove dust. On plaster sand lightly with fine sandpaper before application of Primer S.

Application: Application with roller, brush or sprayer. Avoid runoff of Primer S on the wall. The material dries quickly and, within two hours after application a topcoat can be applied, under ordinary conditions.

Clean-up: Tools can be cleaned with soap and water immediately after use.

Shade: Clear.

Gloss level: semi-glossy (satin).

Contains: A lactic water-based acrylic mixture.

Dilution: with up to 10% water.

Coverage: 7 l/m². The coverage capability is calculated according to the work of a skilled laborer on an infrastructure with an ordinary degree of absorption and may vary according to the working method, surface and weather conditions.

Limitations: Do not apply the material when the temperature is below 7°C or when rain is predicted.

Technical Datasheet

Dry-time:

To recoat: according to the absorption of the surface.

To touch: 30 minutes.

Full cure: 1 hour.

Shelf life and storage: 12 months in a cool, dry place.

Packaging: 1, 4.5 and 18 L.

VOC (Volatile Organic Compounds):

EU limit value for this product (Cat. A/a): 75 g/l (2007) and 30 gr/l (2010). This product contains max 0.1 g/l.

Manufactured by: Nirlat Ltd, Kibbutz Nir-Oz, DN Negev 85122, Israel, www.nirlat.com

Health and Safety precautions: The material does not contain lead. During application it is advisable to wear goggles and ensure that the site is adequately ventilated. If the paint comes in contact with eyes, rinse well under running water and seek medical assistance. Keep the package tightly closed. Do not hang on the handle. Keep away from children. Do not mix materials not recommended by Nirlat.

General Notes: The aforementioned recommendations are not to be perceived as substitute for consultation in writing specific work specifications. All the data and recommendations presented here are based on tests, knowledge and experience that have accumulated in the laboratory and on-site and they are highly reliable. This is not to be interpreted as a general warranty either explicit or implicit. The warranty is for product quality only. The user must examine the suitability thereof for his purposes. We reserve the right to update or change the data without prior notice.